

(11)Publication number:

2001-210995

(43) Date of publication of application: 03.08.2001

(51)Int.CI.

H05K 13/04

(21)Application number: 2000-

(71)Applicant: YAMAHA MOTOR CO LTD

013480

(22)Date of filing:


21.01.2000

(72)Inventor: YAMADA TAKESHI

(54) METHOD AND DEVICE FOR CONTROLLING SURFACE MOUNTING

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent an impact to an electronic part and to shorten the cycle times of a sucking operation and a mounting operation as much as possible. SOLUTION: This control device lowers a sucking head, by which the electronic part is sucked, at a maximum speed by a first speed control unit. When the control device receives the output of a position detection sensor for detecting that the sucking head arrives at a position directly before a substrate, it switches the control of the sucking head to an touching control by a second speed control unit to change a lowering speed to a minimum speed to lower the sucking head at very slow speeds until the sucking head touches the substrate. When the occurrence of a setting



touching pressure is detected by the pressure of a load cell, the device performs a pressing control of pressing the sucking head on the substrate to a target pressure as follows: the lowering speed is once increased to a setting middle speed and then is gradually lowered according to a change in the pressure difference between the target pressure and the detected pressing pressure.

LEGAL STATUS

[Date of request for examination] [Date of sending the examiner's decision of rejection] Kind of final disposal of application other than the examiner's decision of rejection or application converted

BEST AVAILABLE COPY

registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Offi €e